



BONOMI USA, INC. SERIES 171N APPROVALS

| National Standard | Standard Description | Pressure Rating | Sizes |
|--------------------------|--|------------------------|--------------|
| NSF/ANSI 61 | Drinking water system components- Health Affects | 600 WOG | 1/4"-2" |
| CSA [AGAZ21.15] | Manually operated gas valves for appliances, appliance connector valves. For use with national, manufactured, mixed gas, and LP. | 1/2 psi | 1/4"-2" |
| CSA [AGA 3-88] | Manually operated gas valves for use in house piping systems.Approved for use on national, manufactured, and LP gases. | 2psi and 5psi | 1/4"-2" |
| ASME B16.33 | Manually operated mettalic gas valves for use in gas piping systems up to 125psi. | 125psi | 1/2"-2" |
| ASME B16.38 | Manually operated mettalic gas valves for use in piping systems up to 125psi. | 125psi | 2 1/2"-4" |
| CAN/CGA-3.16-M88 | Lever operated non-lubricated gas shut-off. | 125psi | 1/2"-4" |
| ANSI B1.20.1 | American National Standard for pipe threads including NPT. | N/A | All Sizes |
| ANSI B.16.18 | American National Standard for copper alloys and solder joints | N/A | 1/2"-4" |
| MSS SP-110 | Design and test standard for threaded, socket weld,and solder end valves. | N/A | All Sizes |
| U.L. Guide-YSDT | Underwriters Laboratory Guide for gas shut-off valves to 250psi | 250psi | 1/4"-4" |
| U.L. Guide-YRPV | Underwriters Laboratory Guide for gas shut-off valves for use with natural, and manufactured gases, and flammable fluids such as fuel oil, gasoline, and kerosene | 250psi | 1/4"-4" |
| U.L. Guide- VQGU | Underwriters Laboratory Guide for fire protection systems, shut-off/trim, and drain valve | 175psi | 1/2"-4" |

FM-FMRC Class1140 . Standard for approval of quick opening
valves.

600psi

1/4"-4"