

**8E076\*\*\*** - 316 Stainless Steel ANSI 150 Full Port Flanged Wafer Ball Valve with Electric Actuator




720016 Series Ball Valve

Dimensions (in)

8E076

SIZE	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"	8"
A	.500	.750	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	6.00
B	10.5	10.9	13.1	13.8	15.7	16.2	17.9	18.6	20.6	22.1	24.1
C	8.81	8.97	11.0	11.2	12.9	13.2	14.5	14.9	16.3	17.2	18.2
D	4.84	4.84	6.18	6.18	7.28	7.28	8.30	8.30	8.30	8.30	8.74
E	6.45	6.45	7.51	7.51	8.46	8.46	9.33	9.33	9.33	9.33	9.72
F	1.37	1.57	1.81	2.12	2.51	3.22	4.05	4.80	5.98	7.71	9.13
G	3.54	3.93	4.33	5.11	5.51	5.90	6.88	7.48	8.66	9.84	11.8
ACT.	VB015	VB015	VB030	VB030	VB060	VB060	VB110	VB110	VB190	VB190	VB190



*** Voltage Supply Order Suffix				
FOR MOD. VB015	12V AC/DC = 001	24V AC/DC = 002	110V AC = 003	220V AC = 005
FOR MOD. VB30 to 350	24V AC/DC = 002	110 to 240V AC = 004		